

Han CD module, crimp female



Image is for illustration purposes only. Please refer to product description.

Part number	09 14 007 3101
Specification	Han CD module, crimp female
HARTING eCatalogue	https://b2b.harting.com/09140073101

Identification

Category	Modules
Series	Han-Modular®
Type of module	Han® CD module
Size of the module	Single module

Version

Termination method	Crimp termination
Gender	Female
Number of contacts	7
Number of signal contacts	4
Number of power contacts	3
Details	Please order crimp contacts separately.

Technical characteristics

Conductor cross-section	0.14 ... 6 mm ²
Wire outer diameter	≤5 mm
Rated current	40 A
Rated voltage	830 V
Rated impulse voltage	8 kV
Pollution degree	3
Rated current (signal)	10 A
Rated voltage (signal)	830 V
Rated impulse voltage (signal)	8 kV



Pushing Performance
Since 1945

Technical characteristics

Pollution degree (signal)	3
Rated voltage acc. to UL	600 V
Insulation resistance	$>10^{10} \Omega$
Limiting temperature	-40 ... +125 °C
Mating cycles	≥ 500

Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076

Commercial data

Packaging size	2
Net weight	8.99 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140020573



Pushing Performance
Since 1945

Commercial data

eCl@ss

27440217 Module for industrial connectors (power/signals)
