

Han Q 5/0 HighTemp-M-c



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 12 805 3004 |
| Specification | Han Q 5/0 HighTemp-M-c |
| HARTING eCatalogue | https://b2b.harting.com/09128053004 |

Identification

| | |
|----------------|------------------|
| Category | Inserts |
| Series | Han® Q High Temp |
| Identification | 5/0 |

Version

| | |
|--------------------|---|
| Termination method | Crimp termination |
| Gender | Male |
| Size | 3 A |
| Number of contacts | 5 |
| PE contact | Yes |
| Details | Please order crimp contacts separately. Coding pins on request |

Technical characteristics

| | |
|-----------------------------------|--|
| Conductor cross-section | 0.14 ... 2.5 mm ² |
| Rated current | 16 A |
| Rated voltage conductor-earth | 230 V |
| Rated voltage conductor-conductor | 400 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 3 |
| Insulation resistance | >10 ¹⁰ Ω |
| Limiting temperature | -40 ... +200 °C With Han® High Temp components |



Pushing Performance
Since 1945

Technical characteristics

| | |
|---------------|------|
| Mating cycles | ≥500 |
|---------------|------|

Material properties

| | |
|---|------------------------------|
| Material (insert) | Liquid crystal polymer (LCP) |
| Colour (insert) | Black |
| Material flammability class acc. to UL 94 | V-0 |

Specifications and approvals

| | |
|----------------|-----------------------------------|
| Specifications | IEC 60664-1 |
| | IEC 61984 |
| UL / CSA | UL 1977 ECBT2.E235076 |
| | CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 10 |
| Net weight | 15 g |
| Country of origin | Romania |
| European customs tariff number | 85389099 |
| GTIN | 5713140186590 |
| eCl@ss | 27440205 Contact insert for industrial connectors |