KombiSIGN 71 / Audible Devices 645

# Siren element 8 tne 24VAC/DC GY



| | |
|---|---|
| **Part No.:** | **645.790.75** |
| **Series:** | **KombiSIGN 72** |

| MECHANICAL DATA | |
|---|---|
| Height | 54 mm |
| Diameter | 70 mm |
| Materials | PC |
| Housing colour | Grey |
| Protection category | IP65 |
| Working temperature minimum | -20°C |
| Working temperature maximum | +50°C |
| Weight with packaging | 93 g |
| Product weight | 73 g |

| ELECTRICAL DATA | |
|---|---|
| Operating voltage | 24V |
| Operating voltage type | AC/DC |
| Operating voltage frequency | 50Hz |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 24 VDC |
| Rated operational current | 30 mA |
| Rated inrush current | 250 mA |
| Protection class | Protection class 2 |
| Pollution degree | 3 |

| ACOUSTIC DATA | |
|---|---|
| Volume (max) at 1m distance | 102,0 dB (A) |
| Acoustic signal image | Multi-tone |
| Number of tones | 8 tone |
| Volume adjustable | Switch |
| Volume adjustment range | 92 - 102 dB (A) |
| Acoustic service life | 5,000 h minimum |

| APPROVAL DATA | |
|---|---|
| Conforms with CE | Yes |
| WEEE | Yes |
| Conforms with ATEX-directive | No |
| Conforms with CCC | No |
| Conforms with UL | cULus |
| UL Type Rating | Type 12 |
| Conforms with FCC | No |
| Conforms with IC | No |
| EAC certificate available | Yes |


! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

KombiSIGN 71 / Audible Devices 645

# Siren element 8 tne 24VAC/DC GY

| | |
|---|---|
| Conforms with UKCA (Importer) | Yes (WERMA (UK) Ltd.) |
| Conforms with CMIM | No |
| Conforms with AS-I | No |
| ICAO Certification | No |
| Conforms with DNV | No |
| Conforms with RoHS CN | No |
| Conforms with VdS | No |
| MTTF-value [years] | 1676 |

## DRAWING




! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.