


# UMK-32 MDSTB/MKKDS3/R


Order No.: 2970196



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2970196>

VARIOFACE module, with screw connection and COMBICON plug connector, coded, for mounting on NS 35/7.5 or NS 32, no. of positions 32



Commercial data	
GTIN (EAN)	
sales group	I120
Pack	1 pcs.
Customs tariff	85369010
Catalog page information	Page 298 (IF-2009)

### Product notes

WEEE/RoHS-compliant since:  
05/22/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>General data</b>	
Nominal voltage $U_N$	250 V AC/DC
Max. current carrying capacity per branch	3 A
Number of positions	32

Width	112.5 mm
Height	77 mm
Depth	58.5 mm
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Test voltage contact/contact	1.5 kV
Mounting position	Any
Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103

#### Connection data

Connection 1	COMBICON MSTB
Connection in acc. with standard	IEC / EN
Type of connection	Screw connection
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	14
Stripping length	7 mm
Screw thread	M3
Connection 2	PCB connection
Connection in acc. with standard	IEC / EN
Type of connection	Screw connection
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	8 mm
Screw thread	M3

#### Certificates / Approvals



Certification


GOST

---

## Diagrams/Drawings

### Circuit diagram

---



**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;