

# 1-Port European-Style Insert, Coax Coupler (F/F), 22.5 x 45 mm, White

## MODEL NUMBER: N042E-WHM-C1







#### **Highlights**

- Ideal for home theater or VoIP phone in-wall wiring installations
- High-impact plastic construction designed to blend in with your home/office décor
- White insert measures 22.5 x 45 mm for a sleek, professional appearance

### Package Includes

N042E-WHM-C1 1-Port Europe-Style Insert, White

European-style module accepts a compatible coaxial cable for terminating premise audio/video, voice or data applications.

#### **Features**

#### European Module Connects Your Coaxial Audio/Video, Voice or Data Network

This European-style insert with coax cable connector (F/F) is ideal for your premise wiring applications, including home theater, telephones or radio communications. The insert is compatible with Tripp Lite's N042E-WF1 wall plate.

#### High-Impact Construction Designed to Blend In Seamlessly with Your Room

This white module measures 22.5 x 45 millimeters and blends elegantly into any home or office décor for a sleek, professional installation. The ABS plastic construction meets UL 94V-0 flame-retardant standards for protection against fire and high heat.

# **Specifications**

| OVERVIEW                    |  |  |
|-----------------------------|--|--|
| UPC Code                    | 037332268938   |  |
| Technology                  | Cat5/5e; Cat6; Cat6a; DisplayPort; HDBaseT; HDMI; USB 2.0 (High Speed) |  |
| Country/Region              | Europe   |  |
| PHYSICAL                    |  |  |
| Color                       | White  |  |
| Material of Construction    | Brass  |  |
| Total Number of Ports       | 1  |  |
| Unit Dimensions (hwd / in.) | 1.772 x 0.886 x 0.335  |  |



| Finish                              | Matte                                   |  |
|-------------------------------------|---|--|
|                                     |   |  |
| ENVIRONMENTAL                       |   |  |
| Operating Temperature Range         | 14 to 140 F (-10 to 60 C)               |  |
| Storage Temperature Range           | -40 to 154 F (-40 to 68 C)              |  |
| Operating Humidity Range            | 10% to 90% RH, (Non-Condensing)         |  |
| Storage Humidity Range              | 10% to 90% RH, (Non-Condensing)         |  |
|                                     |   |  |
| CONNECTIONS                         |   |  |
| Number of Ports                     | 1                                       |  |
| Side A - Connector 1                | KEYSTONE JACK CUTOUT                    |  |
|                                     |   |  |
| FEATURES & SPECIFICATIONS           |   |  |
| Antibacterial                       | No                                      |  |
|                                     |   |  |
| STANDARDS & COMPLIANCE              |   |  |
| Product Certifications              | UL 94; UL Listed; cUL Listed            |  |
| Product Compliance                  | RoHS; REACH; Trade Agreements Act (TAA) |  |
|                                     |   |  |
| WARRANTY & SUPPORT                  |   |  |
| Product Warranty Period (Worldwide) | Lifetime limited warranty               |  |



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.