



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	400 kcmil
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric
Wire Strip Length	2-3/8 in.
Stud Size	N/A
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	BLUE
Panduit Die Index No. on Barrel	P76
Alternate Industry Die Index No. ( ) on Barrel	(19)



**PANDUIT CORP. TINLEY PARK, ILLINOIS**

LCC400-00W-6  
Copper Lug - Blank Tongue, Long Barrel with Window

01	4/11	JHNU	JHNU
REV	DATE	BY	CHK

REVISED TONGUE WIDTH: 1.39 WAS 1.28  
REVISED TONGUE THICKNESS: .18 WAS .17

DESCRIPTION

ECN

SCALE N/A

DRAWING NO / CAD FILE

LCC400-00W-CUST