

## Han3A RJ45 Cat5 PFT 8p, EMC



Image is for illustration purposes only. Please refer to product description.

Part number	09 45 215 1104
Specification	Han3A RJ45 Cat5 PFT 8p, EMC
HARTING eCatalogue	<a href="https://b2b.harting.com/09452151104">https://b2b.harting.com/09452151104</a>

### Identification

Category	Connectors
Series	RJ45
Element	Panel feed through
Specification	Straight

### Version

Size	Han <sup>®</sup> 3 A
Shielding	Fully shielded, 360° shielding contact
Number of contacts	8
Fixing	Screwable in cover plates

### Technical characteristics

Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s
Limiting temperature	-40 ... +70 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 IP67

### Material properties

Material (hood/housing)	Zinc die-cast
-------------------------	---------------



Pushing Performance  
Since 1945

## Material properties

Surface (hood/housing)	Uncoated
Colour (hood/housing)	Unpainted
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

## Specifications and approvals

Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
PROFINET	Yes

## Commercial data

Packaging size	1
Net weight	54.9 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140059597
eCl@ss	27440101 Rectangular connectors (set)