




THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN CHOGORI PERSONNEL WITHOUT AUTHORIZATION FROM CHOGORI CORP.

REV.	ECN NO.	DESCRIPTION	SIGN	DATE
C1	N/A	Initial Drawing	Xinkunfu	2019/08/13



Specification:

- 1.Operation Temperature: $-40^{\circ}\text{C}\sim 85^{\circ}\text{C}$.
- 2.Insulation Resistance: $100\text{M}\Omega$ At DC500V.
- 3.Contact Resistance: $<30\text{m}\Omega$.
- 4.Waterproof: IP67.
- 5.Mating Cycles: 500 cycles.
- 6.Waterproof Rate: IP67(Mated)
- 7.Seal Nut: Nylon, Black
- 8.Gasket: Silicon, Gray.
- 9.Socket Housing: Nylon, Black
- 10.Plastic Core: CCP PBT, Black
- 11.Baffle: Nylon, Black
- 12.Shield Sheet : Ni Plated
- 13.PCB: Assembly Parts.
- 14.RoHS Compliant.

UNIT: mm		DESCRIPTION RJ45 Panel Mount With Jack 180°(Screw)
TOLERANCE .X ±0.25 .XX ±0.15 .XXX ±0.05 ANGLES ±1°	SCALE: 1:1	SHEET 1 OF 1
REV. C1	SIZE A4	* : Inspection Item

CHOGORI[®]

PART NO 33000000-10	DRAWN BY Xinkunfu	DATE 2019/08/13
DWG NO	CHECKED BY Allen	DATE 2019/08/13
CUSTOMER	APPROVED BY Panson	DATE 2019/08/13