

FO Contact 230HCS Cab.dm 2,8

	,	Part number	20 10 230 5211
		Specification	FO Contact 230HCS Cab.dm 2,8
		HARTING eCatalogue	https://b2b.harting.com/20102305211
dentification			
Category	Contacts		
Type of contact	SC contact		
Description of the contact	for SI fibre (H	ICS [®]) 200/230 μm	
Version			
Gender	Male		
Manufacturing process	Turned conta	cts	
Technical characteristics			
Limiting temperature	-40 +85 °C		
Material properties			
RoHS	compliant		
ELV status	compliant		
China RoHS	е		
REACH Annex XVII substances	Not contained		
REACH ANNEX XIV substances	Not contained		
REACH SVHC substances	Not contained	1	
Commercial data			
Packaging size	1		
Net weight	6.7 g		
	-		
Country of origin	Germany		

Page 1 / 2 | Creation date 2022-09-29 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 20 10 230 5211 FO Contact 230HCS Cab.dm 2,8



Commercial data

GTIN

eCl@ss

5713140133709

27440204 Contact for industrial connectors

Page 2 / 2 | Creation date 2022-09-29 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com