

S1V30120


Text-to-Speech LSI

■ DESCRIPTIONS

The S1V30120 is a highly-integrated solution for speech-enabled devices, featuring TTS(Text-to-Speech), ADCPM decode integrated low power high quality DAC. The chip can be easily integrated with a wide range of host devices and microcontrollers using a message protocol that runs over an SPI link, the S1V30120 makes it possible to create guidance that is easy on the ears.

■ FEATURES

- **TTS (Text-to-Speech)**
 - US English, Castilian/Latin American Spanish.
 - Unconstrained TTS($f_s=11.025\text{kHz}$).
 - Pitch, speaking rate changeable.(online command support)
 - 4 pre-defined voices.
 - No TTS license required.
 - Fonix DECTalk[®] Version 5.
- **Voice Playback**
 - ADPCM decode.
 - Support bitrate : 16kHz(80kbps, 64kbps, 48kbps), 8kHz(40kbps, 32kbps, 24kbps).
- **Host Interface**
 - Synchronous Serial Interface(slave).
 - Command control.
- **High Quality 16-bit monaural DAC**
 - Sampling Rate(f_s): 8, 11.025, 16 kHz.
- **Clock**
 - 32.768KHz.
- **Power Supply**
 - 3.3V (I/O power supply).
 - 1.8V (Core power supply).
- **Package**
 - TQFP13-64pin (10mm x 10mm) 0.5mm Pin Pitch.




Package Pin Allocation

S1V30120

■ Typical Application System

S1V30120 typical application system is described on following figure, host can control S1V30120 using a message protocol over a SPI.
After download a program data and receiving the text data, S1V30120 start output voice from integrated DAC.



NOTICE:

No part of this material may be reproduced or duplicated in any form or by any means without the written permission of Seiko Epson. Seiko Epson reserves the right to make changes to this material without notice. Seiko Epson does not assume any liability of any kind arising out of any inaccuracies contained in this material or due to its application or use in any product or circuit and, further, there is no representation that this material is applicable to products requiring high level reliability, such as, medical products. Moreover, no license to any intellectual property rights is granted by implication or otherwise, and there is no representation or warranty that anything made in accordance with this material will be free from any patent or copyright infringement of a third party. When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations. You are requested not to use, to resell, to export and/or to otherwise dispose of the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes.

All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective companies.

©Seiko Epson Corporation 2015. All rights reserved

SEIKO EPSON CORPORATION

MICRODEVICES OPERATIONS DIVISION

Device Sales & Marketing Department
421-8 Hino, Hino-shi, Tokyo 191-8501, JAPAN
Phone: +81-42-587-5814 FAX: +81-42-587-5117

EPSON semiconductor website

<http://global.epson.com/products/semicon/>

Document code: 410927503
First issue December, 2006
Revised June, 2015 in Japan