



ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

6.9 MHz LC Band Pass Filter

Part Number: AE6.9B5512



Electrical Specifications

Center Frequency: 6.9 MHz
0.3dB Bandwidth: 700 KHz
Insertion Loss: 1.75 dB Max.
Return Loss: 15 dB Min.
Rejection: ≥ 30 dB @ 5.4 MHz
Rejection2: ≥ 48 dB @ 16.8MHz
Impedance: 50 Ohms


Mechanical

Connector Type: PC-Mount
Dimensions: 4.25" X 0.75" x 0.5" approx.

Environmental

Operating Temperature: -25°C to +70°C
Storage Temperature: -40°C to +90°C
Shock: 10 G. 11ms
Vibration: 10 G. 5 to 200Hz

Outline Drawing:



Tolerance: +/-0.01 inches [+/- 0.3mm]

Angles: +/- 1 Deg.

*Tolerance as shown unless otherwise specified in the datasheet electrical specification tables above.


*When max dimensions are called out the above tolerances do not apply as long as it is under the max call out.

70 Outwater Lane Phone: (973) 772-4242
Garfield, NJ 07026 Fax : (973) 321-3941

Email: sales@anatechelectronics.com
Web: www.anatechelectronics.com



Simulation Plot:



Note: This is a simulation Plot. Actual response plot might differ once product is manufactured.