



ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

3250 MHz Suspended Stripline High Pass Filter

Part Number: AE3250SSH6590



Electrical Specifications

Cut Off Frequency: 3.25GHz
Pass Band Frequency: 3.25~22GHz
Pass Band Insertion Loss:
 $\leq 1.5\text{dB @ } 3.25\sim 3.35\text{GHz}$
 $\leq 1.0\text{dB @ } 3.35\sim 22\text{GHz}$
Pass Band VSWR:
 $\leq 1.5:1 @ 3.25\sim 20\text{GHz}$
 $\leq 1.7:1 @ 20\sim 22\text{GHz}$
Stop Band Attenuation: $\geq 50\text{dB @ DC}\sim 2.57\text{GHz}$
Impedance: 50 Ohms
Power Handling: $\leq 15\text{W}$

Mechanical

Mounting Method: Through Holes
Connector Type: SMA-Female
Dimensions: 30.0 x 16.5 x 10.0 mm

Environmental

Operating Temperature: -45° to $+85^\circ$ C
Storage Temperature: -55° to $+95^\circ$ C
Shock: 20 G. 11ms
Vibration: 20 G. 5 to 200 Hz

Outline Drawing:

