



**ANATECH ELECTRONICS INC**  
RF & Microwave Filters & Products

## 44 MHz LC Band Pass Filter

**Part Number: AE44B5545**



### Electrical Specifications

**Center Frequency(CF):** 44 MHz  
**1dB Bandwidth:** 15 MHz Min.  
**Insertion Loss @ CF:** 3.0 dB Max.  
**Return Loss @ 36.6-41.5 MHz:** 14 dB Min.  
**Rejection1:** 45 dB Min. @ 19 MHz  
**Rejection2:** 45 dB Min. @ 69 MHz


### Mechanical

**Connector Type:** PC-Mount  
**Dimensions:** 1.5" X 0.38" x 0.38" .

### Environmental

**Operating Temperature:** -25°C to +70°C  
**Storage Temperature:** -40°C to +90°C  
**Shock:** 10 G. 11ms  
**Vibration:** 10 G. 5 to 200Hz

### Outline Drawing:



Tolerance: +/-0.01 inches [ +/- 0.3mm]

Angles: +/- 1 Deg.

\*Tolerance as shown unless otherwise specified in the datasheet electrical specification tables above.

\*When max dimensions are called out the above tolerances do not apply as long as it is under the max call out.

**70 Outwater Lane Phone: (973) 772-4242**  
**Garfield, NJ 07026 Fax : (973) 321-3941**

**Email: [sales@anatechelectronics.com](mailto:sales@anatechelectronics.com)**  
**Web: [www.anatechelectronics.com](http://www.anatechelectronics.com)**




**ANATECH ELECTRONICS INC**  
RF & Microwave Filters & Products

# 44 MHz LC Band Pass Filter

**Part Number: AE44B5545**



## Response Plot:



1: Mkr (MHz)		dB		2: Mkr (MHz)		dB	
1:	44.00	-0.76		1>	44.00	-26.07	
2:	19.00	-55.48		2:	19.00	-0.05	
3:	69.00	-63.41		3:	69.00	-0.20	
4:	36.50	-0.86		4:	36.50	-17.97	
5>	51.50	-1.57		5:	51.50	-14.55	