



ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

968 MHz LC Band Pass Filter

Part Number: **AE968B5401**



Electrical Specifications

Center Frequency: 968 MHz
3dB Passband: 953 MHz to 983 MHz
Insertion Loss: 8.0 dB Max.
Ripple: 1.0 dB Max.
Return Loss: 14 dB Min.
Rejection1: 50 dB Min. @ 900 MHz
Rejection2: 50dB Min. @ 1040 MHz
Power Handling: 5 W


Mechanical

Mounting Method: PC-Mount
Dimensions: 1.5" X 0.5" x 0.4"

Environmental

Operating Temperature: -25°C to +70°C
Storage Temperature: -40°C to +90°C
Shock: 10 G. 11ms
Vibration: 10 G. 5 to 200Hz

Outline Drawing:



Tolerance: +/-0.01 inches [+/- 0.3mm]

Angles: +/- 1 Deg.

*Tolerance as shown unless otherwise specified in the datasheet electrical specification tables above.


*When max dimensions are called out the above tolerances do not apply as long as it is under the max call out.

70 Outwater Lane Phone: (973) 772-4242
 Garfield, NJ 07026 Fax : (973) 321-3941

Email: sales@anatechelectronics.com
 Web: www.anatechelectronics.com



Simulation Plot:



Note: This is a simulated response plot. Actual performance might differ.