



**NOTE:**  
 1. ORIENT SLEEVE ON BODY BY ALIGNING THE EARS ON THE OUTSIDE OF SLEEVE AS PARALLEL AS POSSIBLE WITH THE TONGUE OF THE BODY BEFORE CLINCHING.  
 2. BAND TO BE COVERED, APPROX AS SHOWN, AFTER TUCK IS MADE.

LOC	REV	DATE	APP	DATE
T	REV/0720-0254-93	10/14/93		
S	REV/PER G-5049	10/26/89		
M	REV/2-16-2581/REV G-4617	10/17/87		
N	REV/2-11-1185/REV A-9909	10/13/83		
P	REV/PER P-8965	10/13/81		
M	REV/PER P-8965	10/13/81		
M	REV/PER P-8965	10/13/81		

REV	DATE	APP	DATE
1			
2			
3			
4			

AMP 3306 REV 8-78 8 7 6 5 4 3 2 1

OBSOLETE

QTY REQD PER ASSY	DWG SIZE	PART NO	DESCRIPTION	ITEM NO
1	25803-3	SLEEVE ASS'Y	1	
1	115-11001	TAPE SPEC.	2	
1	321665	BODY		

DIMENSIONS IN INCHES. TOLERANCES UNLESS OTHERWISE SPECIFIED:  
 2 PL DEC ± —  
 3 PL DEC ± —  
 4 PL DEC ± —  
 ANGLES ± —  
 SURF TEXTURE: —  
 REMOVE BURRS, BREAK SHARP EDGES, DISR MAX

MATERIAL: — HEAT TREAT: — FINISH: —  
 NAME: —  
 SCALE: N.T.S. DWG NO: 321669 SHEET: 1/1 REV: T

A

B

C

D