

74AC139 • 74ACT139

Dual 1-of-4 Decoder/Demultiplexer

General Description

The AC/ACT139 is a high-speed, dual 1-of-4 decoder/demultiplexer. The device has two independent decoders, each accepting two inputs and providing four mutually-exclusive active-LOW outputs. Each decoder has an active-LOW Enable input which can be used as a data input for a 4-output demultiplexer. Each half of the AC/ACT139 can be used as a function generator providing all four minterms of two variables.

Features


- I_{cc} reduced by 50%
- Multifunction capability
- Two completely independent 1-of-4 decoders
- Active LOW mutually exclusive outputs
- Outputs source/sink 24 mA
- ACT139 has TTL-compatible inputs

Ordering Code:

Order Number	Package Number	Package Description
74AC139SC	M16A	16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150" Narrow Body
74AC139SJ	M16D	16-Lead Small Outline Package (SOIC), EIAJ Type II, 5.3mm Wide
74AC139MTC	MTC16	16-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide
74AC139PC	N16E	16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide
74ACT139SC	M16A	16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150" Narrow Body
74ACT139SJ	M16D	16-Lead Small Outline Package (SOIC), EIAJ Type II, 5.3mm Wide
74ACT139MTC	MTC16	16-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide
74ACT139PC	N16E	16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide

Device also available in Tape and Reel. Specify by appending suffix letter "X" to the ordering code.

Connection Diagram





Pin Descriptions

Pin Names	Description
A ₀ , A ₁	Address Inputs
Ē	Enable Inputs
O ₀ –O ₃	Outputs

FACT™ is a trademark of Fairchild Semiconductor Corporation.

Logic Symbols



Functional Description

The AC/ACT139 is a high-speed dual 1-of-4 decoder/demultiplexer. The device has two independent decoders, each of which accepts two binary weighted inputs (A_0-A_1) and provides four mutually exclusive active-LOW outputs ($\bar{O}_0-\bar{O}_3$). Each decoder has an active-LOW enable (\bar{E}). When \bar{E} is HIGH all outputs are forced HIGH. The enable can be used as the data input for a 4-output demultiplexer application. Each half of the AC/ACT139 generates all four minterms of two variables. These four minterms are useful in some applications, replacing multiple gate functions as shown in Figure 1, and thereby reducing the number of packages required in a logic network.





FIGURE 1. Gate Functions (Each Half)

Truth Table

Inputs			Outputs			
\bar{E}	A_0	A_1	\bar{O}_0	\bar{O}_1	\bar{O}_2	\bar{O}_3
H	X	X	H	H	H	H
L	L	L	L	H	H	H
L	H	L	H	L	H	H
L	L	H	H	H	L	H
L	H	H	H	H	H	L

H = HIGH Voltage Level
L = LOW Voltage Level
X = Immortal

Logic Diagram

Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

Absolute Maximum Ratings ^(Note 1)		Recommended Operating Conditions							
Supply Voltage (V_{CC})	-0.5V to +7.0V	Supply Voltage (V_{CC})							
DC Input Diode Current (I_{IK})		AC	2.0V to 6.0V						
$V_I = -0.5V$	-20 mA	ACT	4.5V to 5.5V						
$V_I = V_{CC} + 0.5V$	+20 mA								
DC Input Voltage (V_I)	-0.5V to $V_{CC} + 0.5V$	Input Voltage (V_I)	0V to V_{CC}						
DC Output Diode Current (I_{OK})		Output Voltage (V_O)	0V to V_{CC}						
$V_O = -0.5V$	-20 mA	Operating Temperature (T_A)	-40°C to +85°C						
$V_O = V_{CC} + 0.5V$	+20 mA	Minimum Input Edge Rate ($\Delta V/\Delta t$)							
DC Output Voltage (V_O)	-0.5V to $V_{CC} + 0.5V$	AC Devices							
DC Output Source or Sink Current (I_O)	± 50 mA	V_{IN} from 30% to 70% of V_{CC}							
DC V_{CC} or Ground Current per Output Pin (I_{CC} or I_{GND})	± 50 mA	V_{CC} @ 3.3V, 4.5V, 5.5V	125 mV/ns						
Storage Temperature (T_{STG})	-65°C to +150°C	Minimum Input Edge Rate ($\Delta V/\Delta t$)							
Junction Temperature (T_J)		ACT Devices							
PDIP	140°C	V_{IN} from 0.8V to 2.0V							
		V_{CC} @ 4.5V, 5.5V	125 mV/ns						
Note 1: Absolute maximum ratings are those values beyond which damage to the device may occur. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. Fairchild does not recommend operation of FACT™ circuits outside databook specifications.									
DC Electrical Characteristics for AC									
Symbol	Parameter	V_{CC}	$T_A = +25^\circ C$		$T_A = -40^\circ C$ to $+85^\circ C$	Units	Conditions		
		(V)	Typ	Guaranteed Limits					
V_{IH}	Minimum High Level Input Voltage	3.0 4.5 5.5	1.5 2.25 2.75	2.1 3.15 3.85	2.1 3.15 3.85	V	$V_{OUT} = 0.1V$ or $V_{CC} - 0.1V$		
	V_{IL}	Maximum Low Level Input Voltage	3.0 4.5 5.5	1.5 2.25 2.75	0.9 1.35 1.65		0.9 1.35 1.65	V	$V_{OUT} = 0.1V$ or $V_{CC} - 0.1V$
		V_{OH}	Minimum High Level Output Voltage	3.0 4.5 5.5	2.99 4.49 5.49		2.9 4.4 5.4		2.9 4.4 5.4
V_{OL}			3.0 4.5 5.5		2.56 3.86 4.86	2.46 3.76 4.76	V		$V_{IN} = V_{IL}$ or V_{IH} $I_{OH} = -12\ mA$ $I_{OH} = -24\ mA$ $I_{OH} = -24\ mA$ (Note 2)
	I_{IN} (Note 4)		Maximum Input Leakage Current	5.5		± 0.1		V	$I_{OUT} = 50\ \mu A$
			5.5		± 1.0	μA			$V_I = V_{CC}, GND$
			5.5						
			I_{OLD}	Minimum Dynamic	5.5		75	mA	$V_{OLD} = 1.65V$ Max
		I_{OHD}	Output Current (Note 3)	5.5		-75	mA	$V_{OHD} = 3.85V$ Min	
I_{CC} (Note 4)		Maximum Quiescent Supply Current	5.5		4.0	40.0	μA		
Note 2: All outputs loaded; thresholds on input associated with output under test.									
Note 3: Maximum test duration 2.0 ms, one output loaded at a time.									
Note 4: I_{IN} and I_{CC} @ 3.0V are guaranteed to be less than or equal to the respective limit @ 5.5V V_{CC} .									

DC Electrical Characteristics for ACT

Symbol	Parameter	V _{CC} (V)	T _A = +25°C		T _A = -40°C to +85°C	Units	Conditions
			Typ	Guaranteed Limits			
V _{IH}	Minimum High Level Input Voltage	4.5 5.5	1.5 1.5	2.0 2.0	2.0 2.0	V	V _{OUT} = 0.1V or V _{CC} - 0.1V
V _{IL}	Maximum Low Level Input Voltage	4.5 5.5	1.5 1.5	0.8 0.8	0.8 0.8	V	V _{OUT} = 0.1V or V _{CC} - 0.1V
V _{OH}	Minimum High Level Output Voltage	4.5 5.5	4.49 5.49	4.4 5.4	4.4 5.4	V	I _{OUT} = -50 µA
		4.5 5.5		3.86 4.86	3.76 4.76	V	V _{IN} = V _{IL} or V _{IH} I _{OH} = -24 mA I _{OH} = -24 mA (Note 5)
		4.5 5.5		0.36 0.36	0.44 0.44	V	V _{IN} = V _{IL} or V _{IH} I _{OL} = 24 mA I _{OL} = 24 mA (Note 5)
V _{OL}	Maximum Low Level Output Voltage	4.5 5.5	0.001 0.001	0.1 0.1	0.1 0.1	V	I _{OUT} = 50 µA
		4.5 5.5		0.36 0.36	0.44 0.44	V	V _{IN} = V _{IL} or V _{IH} I _{OL} = 24 mA I _{OL} = 24 mA (Note 5)
I _{IN}	Maximum Input Leakage Current	5.5		±0.1	±1.0	µA	V _I = V _{CC} , GND
I _{CCT}	Maximum I _{CC} /Input	5.5	0.6		1.5	mA	V _I = V _{CC} - 2.1V
I _{OLD}	Minimum Dynamic Output Current (Note 6)	5.5 5.5			75 -75	mA	V _{OLD} = 1.65V Max V _{OHD} = 3.85V Min
I _{CC}	Maximum Quiescent Supply Current	5.5		4.0	40.0	µA	V _{IN} = V _{CC} or GND

Note 5: All outputs loaded; thresholds on input associated with output under test.

Note 6: Maximum test duration 2.0 ms, one output loaded at a time.

AC Electrical Characteristics for AC

Symbol	Parameter	V _{CC} (V) (Note 7)	T _A = +25°C C _L = 50 pF		T _A = -40°C to +85°C C _L = 50 pF		Units	
			Min	Typ	Max	Min		
t _{PLH}	Propagation Delay A _n to \bar{O}_n	3.3 5.0	4.0 3.0	8.0 6.5	11.5 8.5	3.5 2.5	13.0 9.5	ns
t _{PHL}	Propagation Delay A _n to \bar{O}_n	3.3 5.0	3.0 2.5	7.0 5.5	10.0 7.5	2.5 2.0	11.0 8.5	ns
t _{PLH}	Propagation Delay \bar{E}_n to \bar{O}_n	3.3 5.0	4.5 3.5	9.5 7.0	12.0 8.5	3.5 3.0	13.0 10.0	ns
t _{PHL}	Propagation Delay \bar{E}_n to \bar{O}_n	3.3 5.0	4.0 2.5	8.0 6.0	10.0 7.5	3.0 2.5	11.0 8.5	ns

Note 7: Voltage Range 3.3 is 3.3V ±0.3V.

Voltage Range 5.0 is 5.0V ±0.5V

AC Electrical Characteristics for ACT

Symbol	Parameter	V _{CC} (V) (Note 8)	T _A = +25°C C _L = 50 pF			T _A = -40°C to +85°C C _L = 50 pF			Units
			Min	Typ	Max	Min	Max		
t _{PLH}	Propagation Delay A _n to \bar{O}_n	5.0	1.5	6.0	8.5	1.5	9.5	ns	
t _{PHL}	Propagation Delay A _n to \bar{O}_n	5.0	1.5	6.0	9.5	1.5	10.5	ns	
t _{PLH}	Propagation Delay \bar{E}_n to \bar{O}_n	5.0	2.5	7.0	10.0	2.0	11.0	ns	
t _{PHL}	Propagation Delay \bar{E}_n to \bar{O}_n	5.0	2.0	7.0	9.5	1.5	10.5	ns	



Note 8: Voltage Range 5.0 is 5.0V ±0.5V

Capacitance



Symbol	Parameter	Typ	Units	Conditions
C _{IN}	Input Capacitance	4.5	pF	V _{CC} = OPEN
C _{PD}	Power Dissipation Capacitance	40.0	pF	V _{CC} = 5.0V

Physical Dimensions


inches (millimeters) unless otherwise noted




**16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150" Narrow Body
Package Number M16A**



**16-Lead Small Outline Package (SOP), EIAJ Type II, 5.3mm Wide
Package Number M16D**

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)

74AC139 • 74ACT139 Dual 1-of-4 Decoder/Demultiplexer



**16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide
Package Number N16E**

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com