



**PANEL CUTOUT**

**SPECIFICATIONS:**  
 Housing: Thermoplastic, UL-94V-0 rated  
 Contacts: Copper alloy  
 Electrical ratings: 660W, 600V  
 Max. Operating temperature: 120°C  
 Applicable Wire type: 18AWG solid copper  
 Conductor strip length: 9.5mm  
 Applicable Panel thickness: 1.0 - 1.5mm  
 For T8 bulb type  
 For G13 Base  
 For Rapid Start (I)

**Certifications:**  
 UL 542  
 UL 496  
 CSA 22.2 / 43



RoHS  
 COMPLIANT

**REVISIONS**

REV	DATE	CHANGE	CHKG	CHKD	APPR
A	11/16/17	UPDATED DRAWING		PB	

**TOLERANCE**  
 UNLESS OTHERWISE SPECIFIED  
 X ± 1  
 X.X ± 0.4  
 X.XX ± 0.13

**Power Dynamics, Inc.**  
 Phone: 973 560-0019 Whippany, New Jersey Fax: 973 560-0076

**PART:** FLUORESCENT / LED T8 LAMPHOLDER FOR G13 BASE  
 MEDIUM BI-PIN; NON-SHUNTED; TURN TYPE WITH LOCK  
 FOR RAPID START; MEDIUM HEIGHT

<b>DRAWN BY:</b> PB	<b>DATE:</b> 10/26/17
<b>CHECK BY:</b>	<b>DATE:</b>
<b>APPR BY:</b>	<b>DATE:</b>

<b>PART #:</b> PD-FL-18-11	<b>SHEET</b> 1 of 1
<b>SIZE:</b> A	ALL DIMENSIONS FOR REFERENCE ONLY DIMENSIONS ARE IN MILLIMETERS
<b>SCALE:</b> NTS	