



Circular Connectors IP68
Circular Connectors AC 167 micro
AC 167 REST/2 M16



panel mount plug, 2 pole, voltage rating: 500 V, current rating: 10 A

Order Info

reference number (ref.no.)	72876216
PU	200
EAN	4028012133833

Type

type	panel mount plug
number of poles	2 pole
clamping units per pole	1
colour	black
coding	1 (mains)
cross-section rating	1.0 mm ²
protection against incorrect plugging	yes
latch	yes

Technical Data

voltage rating	500 V
current rating	10 A
impulse voltage rating	4.0 kV
contact material	brass
core cross-section min.	0.25 mm ²
core cross-section max.	1.0 mm ²
protection class	SK II
flammability rating	V-0
max. ambient temperature operation	60 °C
IP code	IP66/IP68/IP69
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	10.0 mm
dismantling length	20.0 mm
assembly contact screw	M2 - max. τ 0,2 Nm
wall thickness max.	7.0 mm

housing hole diameter	M16
------------------------------	-----

tightening torque lock nut	1,5 Nm
-----------------------------------	--------

Accessories

AC 167 RVKS M16	729042
------------------------	--------

AC 167 RWZ/2	729044
---------------------	--------