

## **MM54HC299/MM74HC299**

### **8-Bit TRI-STATE® Universal Shift Register**

#### **General Description**

This 8-bit TRI-STATE shift/storage register utilizes advanced silicon-gate CMOS technology. Along with the low power consumption and high noise immunity of standard CMOS integrated circuits, it has the ability to drive 15 LS-TTL loads. This circuit also features operating speeds comparable to the equivalent low power Schottky device.

The MM54HC299/MM74HC299 features multiplexed inputs/outputs to achieve full 8-bit data handling in a single 20-pin package. Due to the large output drive capability and TRI-STATE feature, this device is ideally suited for interfacing with bus lines in a bus oriented system.

Two function select inputs and two output control inputs are used to choose the mode of operation as listed in the function table. Synchronous parallel loading is accomplished by taking both function select lines S0 and S1 high. This places the TRI-STATE outputs in a high impedance state, which


permits data applied to the input/output lines to be clocked into the register. Reading out of the register can be done while the outputs are enabled in any mode. A direct overriding CLEAR input is provided to clear the register whether the outputs are enabled or disabled.

The 54HC/74HC logic family is functionally as well as pinout compatible with the standard 54LS/74LS logic family. All inputs are protected from damage due to static discharge by internal diode clamps to V<sub>CC</sub> and ground.

#### **Features**

- Typical operating frequency 40 MHz
- Typical propagation delay: 20 ns
- Low quiescent current: 80  $\mu$ A maximum (74HC)
- High output drive for bus applications
- Low quiescent current: 1  $\mu$ A maximum

#### **Connection Diagram**



TL/F/5207-1

**Order Number MM54HC299 or MM74HC299**

TRI-STATE® is a registered trademark of National Semiconductor Corporation.

<b>Absolute Maximum Ratings</b> (Notes 1 & 2)								
If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.								
Supply Voltage ( $V_{CC}$ )	−0.5 to + 7.0V							
DC Input Voltage ( $V_{IN}$ )	−1.5 to $V_{CC}$ + 1.5V							
DC Output Voltage ( $V_{OUT}$ )	−0.5 to $V_{CC}$ + 0.5V							
Clamp Diode Current ( $I_{CD}$ )	±20 mA							
DC Output Current, per pin ( $I_{OUT}$ )	±25 mA ( $Q_A$ , $Q_H$ ) ±35 mA (others)							
DC $V_{CC}$ or GND Current, per pin ( $I_{CC}$ )	±70 mA							
Storage Temperature Range ( $T_{STG}$ )	−65°C to + 150°C							
Power Dissipation ( $P_D$ ) (Note 3)	600 mW							
S.O. Package only	500 mW							
Lead Temp. ( $T_L$ ) (Soldering 10 seconds)	260°C							
<b>DC Electrical Characteristics</b> (Note 4)								
Symbol	Parameter	Conditions	$V_{CC}$	$T_A = 25^\circ C$		$74HC$	$54HC$	Units
				Typ		$T_A = -40$ to $85^\circ C$	$T_A = -55$ to $125^\circ C$	
$V_{IH}$	Minimum High Level Input Voltage		2.0V 4.5V 6.0V	1.5 3.15 4.2	1.5 3.15 4.2	1.5 3.15 4.2	1.5 3.15 4.2	V
$V_{IL}$	Maximum Low Level Input Voltage**		2.0V 4.5V 6.0V	0.5 1.35 1.8	0.5 1.35 1.8	0.5 1.35 1.8	0.5 1.35 1.8	V
$V_{OH}$	Minimum High Level Output Voltage	$V_{IN} = V_{IH}$ or $V_{IL}$ $ I_{OUT}  \leq 20 \mu A$	2.0V 4.5V 6.0V	2.0 4.5 6.0	1.9 4.4 5.9	1.9 4.4 5.9	1.9 4.4 5.9	V
	$Q_A$ & $Q_H$ Outputs	$V_{IN} = V_{IH}$ or $V_{IL}$ $ I_{OUT}  \leq 4.0$ mA $ I_{OUT}  \leq 5.2$ mA	4.5V 6.0V	4.2 5.7	3.98 5.48	3.84 5.34	3.7 5.2	V
	A/ $Q_A$ thru H/ $Q_H$ Outputs	$V_{IN} = V_{IH}$ or $V_{IL}$ $ I_{OUT}  \leq 6.0$ mA $ I_{OUT}  \leq 7.8$ mA	4.5V 6.0V	4.2 5.7	3.98 5.48	3.84 5.34	3.7 5.2	V
$V_{OL}$	Maximum Low Level Output Voltage	$V_{IN} = V_{IH}$ or $V_{IL}$ $ I_{OUT}  \leq 20 \mu A$	2.0V 4.5V 6.0V	0 0 0	0.1 0.1 0.1	0.1 0.1 0.1	0.1 0.1 0.1	V
	$Q_A$ and $Q_H$ Outputs	$V_{IN} = V_{IH}$ or $V_{IL}$ $ I_{OUT}  \leq 4$ mA $ I_{OUT}  \leq 5.2$ mA	4.5V 6.0V	0.2 0.2	0.26 0.26	0.33 0.33	0.4 0.4	V
	A/ $Q_A$ thru H/ $Q_H$ Outputs	$V_{IN} = V_{IH}$ or $V_{IL}$ $ I_{OUT}  \leq 6$ mA $ I_{OUT}  \leq 7.8$ mA	4.5V 6.0V	0.2 0.2	0.26 0.26	0.33 0.33	0.4 0.4	V
$I_{IN}$	Maximum Input Current	$V_{IN} = V_{CC}$ or GND	6.0V	±0.1	±1.0	±1.0	±1.0	$\mu A$
$I_{OZ}$	Maximum TRI-STATE Output Leakage Current	$V_{OUT} = V_{CC}$ or GND $G = V_{IH}$	6.0V	±0.5	±0.5	±1.0	±1.0	$\mu A$
$I_{CC}$	Maximum Quiescent Supply Current	$V_{IN} = V_{CC}$ or GND $I_{OUT} = 0 \mu A$	6.0V	8.0	80	160	160	$\mu A$
Note 1: Absolute Maximum Ratings are those values beyond which damage to the device may occur.								
Note 2: Unless otherwise specified all voltages are referenced to ground.								
Note 3: Power Dissipation temperature derating — plastic "N" package: − 12 mW/°C from 65°C to 85°C; ceramic "J" package: − 12 mW/°C from 100°C to 125°C.								
Note 4: For a power supply of $5V \pm 10\%$ the worst-case output voltages ( $V_{OH}$ and $V_{OL}$ ) occur for HC at 4.5V. Thus the 4.5V values should be used when designing with this supply. Worst-case $V_{IH}$ and $V_{IL}$ occur at $V_{CC} = 5.5V$ and 4.5V respectively. (The $V_{IH}$ value at 5.5V is 3.85V.) The worst-case leakage current ( $I_{IN}$ , $I_{CC}$ , and $I_{OZ}$ ) occur for CMOS at the higher voltage and so the 6.0V values should be used.								
** $V_{IL}$ limits are currently tested at 20% of $V_{CC}$ . The above $V_{IL}$ specification (30% of $V_{CC}$ ) will be implemented no later than Q1, CY'89.								

**AC Electrical Characteristics**  $V_{CC} = 5V$ ,  $T_A = 25^\circ C$ ,  $t_r = t_f = 6 \text{ ns}$ ,  $C_L = 45 \text{ pF}$

Symbol	Parameter		Conditions	Typ	Guaranteed Limit	Units
$f_{MAX}$	Maximum Operating Frequency			40	25	MHz
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay, Clock to $Q_A'$ or $Q_H'$			25	35	ns
$t_{PHL}$	Maximum Propagation Delay, Clear to $Q_A'$ or $Q_H'$			39	40	ns
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay, Clock to $Q_A - Q_H$		$C_L = 45 \text{ pF}$	25	35	ns
$t_{PHL}$	Maximum Propagation Delay, Clear to $Q_A - Q_H$		$C_L = 45 \text{ pF}$	28	40	ns
$t_{PZL}, t_{PZH}$	Maximum Enable Time		$C_L = 45 \text{ pF}$ $R_L = 1 \text{ k}\Omega$	10	35	ns
$t_{PHZ}, t_{PLZ}$	Maximum Disable Time		$C_L = 5 \text{ pF}$ $R_L = 1 \text{ k}\Omega$	18	25	ns
$t_S$	Minimum Setup Time	Select			20	ns
		Data			20	ns
$t_H$	Minimum Hold Time	Select			0	ns
		Data			0	ns
$t_W$	Minimum Pulse Width			12	20	ns
$t_{REM}$	Clear Removal Time				10	ns

**AC Electrical Characteristics**  $C_L = 50 \text{ pF}$ ,  $t_r = t_f = 6 \text{ ns}$  unless otherwise specified

Symbol	Parameter	Conditions	$V_{CC}$	$T_A = 25^\circ C$		$74HC$	$54HC$	Units
				Typ		$T_A = -40 \text{ to } 85^\circ C$	$T_A = -55 \text{ to } 125^\circ C$	
$f_{MAX}$	Maximum Operating Frequency		2.0V 4.5V 6.0V	5 25 29		4 20 23	3.5 18 20	MHz MHz MHz
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay, Clock to $Q_A'$ or $Q_H'$		2.0V 4.5V 6.0V	15 27 25	170 38 35	210 48 44	240 54 49	ns ns ns
$t_{PHL}$	Maximum Propagation Delay, Clear to $Q_A'$ or $Q_H'$		2.0V 4.5V 6.0V	70 30 26	200 44 38	250 55 46	280 62 52	ns ns ns
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay, Clock to $Q_A - Q_H$	$C_L = 50 \text{ pF}$	2.0V 2.0V	65 100	170 206	210 260	240 295	ns ns
		$C_L = 150 \text{ pF}$	4.5V 4.5V	27 34	38 46	48 57	54 66	ns ns
		$C_L = 50 \text{ pF}$	6.0V 6.0V	25 31	35 39	44 49	49 55	ns ns
		$C_L = 150 \text{ pF}$						
$t_{PHL}$	Maximum Propagation Delay, Clear to $Q_A - Q_H$	$C_L = 50 \text{ pF}$	2.0V 2.0V	70 110	200 236	250 295	280 325	ns ns
		$C_L = 150 \text{ pF}$	4.5V 4.5V	30 37	44 52	55 65	62 75	ns ns
		$C_L = 50 \text{ pF}$	6.0V 6.0V	26 32	38 46	46 57	52 64	ns ns
		$C_L = 150 \text{ pF}$						

### AC Electrical Characteristic (Continued) $C_L = 50 \text{ pF}$ , $t_r = t_f = 6 \text{ ns}$ unless otherwise specified

Symbol	Parameter	Conditions	V <sub>CC</sub>	T <sub>A</sub> = 25°C		74HC	54HC	Units
				Typ	Guaranteed Limits	T <sub>A</sub> = -40 to 85°C	T <sub>A</sub> = -55 to 125°C	
t <sub>PZH</sub> , t <sub>PZL</sub>	Maximum Output Enable	R <sub>L</sub> = 1 kΩ						
		C <sub>L</sub> = 50 pF	2.0V	70	160	200	225	ns
		C <sub>L</sub> = 150 pF	2.0V	90	220	275	310	ns
		C <sub>L</sub> = 50 pF	4.5V	22	32	40	45	ns
		C <sub>L</sub> = 150 pF	4.5V	30	44	55	62	ns
t <sub>PHZ</sub> , t <sub>PLZ</sub>	Maximum Output Disable Time	C <sub>L</sub> = 50 pF	6.0V	19	28	34	38	ns
		C <sub>L</sub> = 150 pF	6.0V	24	47	47	51	ns
		R <sub>L</sub> = 1 kΩ	2.0V	70	160	200	225	ns
t <sub>S</sub>	Minimum Setup Time, Data Select S <sub>L</sub> or S <sub>R</sub>	C <sub>L</sub> = 50 pF	4.5V	22	32	40	45	ns
		C <sub>L</sub> = 150 pF	6.0V	19	28	34	38	ns
		2.0V	4.5V	100	125	140	ns	ns
t <sub>H</sub>	Minimum Hold Time, Data Select S <sub>L</sub> or S <sub>R</sub>	4.5V	6.0V	20	25	28	ns	ns
		6.0V	17	21	25	28	ns	ns
		2.0V	4.5V	0	0	0	0	ns
t <sub>REM</sub>	Minimum Clear Removal Time	6.0V	0	10	10	10	ns	ns
		2.0V	4.5V	10	10	10	ns	ns
		6.0V	10	10	10	10	ns	ns
t <sub>W</sub>	Minimum Pulse Width, Clock and Clear	2.0V	2.0V	100	125	140	ns	ns
		4.5V	4.5V	20	25	28	ns	ns
		6.0V	6.0V	17	21	25	ns	ns
t <sub>r</sub> , t <sub>f</sub>	Maximum Input Rise and Fall Time	2.0V	2.0V	1000	1000	100	ns	ns
		4.5V	4.5V	500	500	500	ns	ns
		6.0V	6.0V	400	400	400	ns	ns
t <sub>THL</sub> , t <sub>TLH</sub>	Maximum Output Rise and Fall Time, Clock	2.0V	2.0V	60	75	90	ns	ns
		4.5V	4.5V	12	15	18	ns	ns
		6.0V	6.0V	10	13	15	ns	ns
C <sub>PD</sub>	Power Dissipation Capacitance	Outputs Enabled Outputs Disabled		240 110				pF pF
C <sub>IN</sub>	Maximum Input Capacitance Capacitance			5	10	10	10	pF
C <sub>OUT</sub>	Maximum TRI-STATE Output Capacitance			15	20	20	20	pF


Note 5: C<sub>PD</sub> determines the no load dynamic power consumption, P<sub>D</sub> = C<sub>PD</sub> V<sub>CC</sub><sup>2</sup> f + I<sub>CC</sub> V<sub>CC</sub>, and the no load dynamic current consumption, I<sub>S</sub> = C<sub>PD</sub> V<sub>CC</sub> f + I<sub>CC</sub>.

### Function Table

Mode	Inputs				Inputs/Outputs								Outputs				
	Clear	Function Select	Output Control	Clock	Serial SL SR	A/Q <sub>A</sub>	B/Q <sub>B</sub>	C/Q <sub>C</sub>	D/Q <sub>D</sub>	E/Q <sub>E</sub>	F/Q <sub>F</sub>	G/Q <sub>G</sub>	H/Q <sub>H</sub>	Q <sub>A'</sub>	Q <sub>H'</sub>		
						S <sub>1</sub>	S <sub>0</sub>	G <sub>1</sub> †	G <sub>2</sub> †								
Clear	L L	X L	L X	L L	X X	X X	X X	L L									
Hold	H H	L X	L L	L L	X L or H	X X	X X	Q <sub>A0</sub> Q <sub>A0</sub>	Q <sub>B0</sub> Q <sub>B0</sub>	Q <sub>C0</sub> Q <sub>C0</sub>	Q <sub>D0</sub> Q <sub>D0</sub>	Q <sub>E0</sub> Q <sub>E0</sub>	Q <sub>F0</sub> Q <sub>F0</sub>	Q <sub>G0</sub> Q <sub>G0</sub>	Q <sub>H0</sub> Q <sub>H0</sub>	Q <sub>A0</sub> Q <sub>A0</sub>	Q <sub>H0</sub> Q <sub>H0</sub>
Shift Right	H H	L L	H H	L L	↑ ↑	X X	H L	Q <sub>A</sub> Q <sub>An</sub>	Q <sub>B</sub> Q <sub>Bn</sub>	Q <sub>C</sub> Q <sub>Cn</sub>	Q <sub>D</sub> Q <sub>Dn</sub>	Q <sub>E</sub> Q <sub>En</sub>	Q <sub>F</sub> Q <sub>Fn</sub>	Q <sub>G</sub> Q <sub>Gn</sub>	Q <sub>H</sub> Q <sub>Gn</sub>	H L	Q <sub>GN</sub> Q <sub>GN</sub>
Shift Left	H H	H L	L L	L L	↑ ↑	H L	X X	Q <sub>B</sub> Q <sub>Bn</sub>	Q <sub>C</sub> Q <sub>Cn</sub>	Q <sub>D</sub> Q <sub>Dn</sub>	Q <sub>E</sub> Q <sub>En</sub>	Q <sub>F</sub> Q <sub>Fn</sub>	Q <sub>G</sub> Q <sub>Gn</sub>	Q <sub>H</sub> Q <sub>Hn</sub>	H L	Q <sub>Bn</sub> Q <sub>Bn</sub>	H L
Load	H	H	H	X	X	↑	X	X	a	b	c	d	e	f	g	h	a h


†When one or both controls are high the eight input/output terminals are disabled to the high-impedance state; however, sequential operation or clearing of the register is not affected.

## Logic Diagram



# MM54HC299/MM74HC299 8-Bit TRI-STATE Universal Shift Register


## Physical Dimensions inches (millimeters)



J20A (FEV M)

Order Number MM54HC299J or MM74HC299J

NS Package J20A



N20A (REV G)

Order Number MM74HC299N

NS Package N20A

## LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



**National Semiconductor  
Corporation**  
1111 West Bardin Road  
Arlington, TX 76017  
Tel: (800) 272-9959  
Fax: (800) 737-7018

**National Semiconductor  
Europe**

Fax: (+49) 0-180-530 85 86  
Email: cnjwge@tevm2.nsc.com  
Deutsch Tel: (+49) 0-180-530 85 85  
English Tel: (+49) 0-180-532 78 32  
Français Tel: (+49) 0-180-532 93 58  
Italiano Tel: (+49) 0-180-534 16 80

**National Semiconductor  
Hong Kong Ltd.**  
13th Floor, Straight Block,  
Ocean Centre, 5 Canton Rd.  
Tsimshatsui, Kowloon  
Hong Kong  
Tel: (852) 2737-1600  
Fax: (852) 2736-9960

**National Semiconductor  
Japan Ltd.**  
Tel: 81-043-299-2309  
Fax: 81-043-299-2408

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.