

# ILC7262

## Dual CMOS LDO

### Features

- All-CMOS design in an 8-lead SOIC package
- $\pm 2\%$  precision outputs
- $2.2\mu\text{A}$  of  $I_q$
- Short-circuit protected outputs
- Voltage options allow:
  - Dual 50mA 5.0 & 3.3V Regulator
  - Dual 50mA 5.0 & 3.0V Regulator
  - Dual 125mA 5V to 3.0V & 3.3V Converter

### Applications

- Battery-powered Equipment
- Portable communications
- PDAs and palmtops


### Description

Dual 125mA CMOS LDO in an SO-8 package. This part offers 120mV dropout voltage on each output at 100mA typical (5V part), and nearly zero dropout below 5mA. Each output is independently short-circuit protected.


Its all-CMOS design means that only  $2.2\mu\text{A}$  of current is required to run the part.

$\pm 2\%$  accurate outputs come in a number of configurations, to allow for flexible yet compact portable system designs.

### Block Diagram



## Pin Assignments



## Absolute Maximum Ratings

Parameter	Min.	Max.	Unit
Input Voltage	$V_{IN}$	12	V
Output Current	$I_{OUT}$	500	mA
Output Voltage	$V_{OUT}$	$V_{SS}-0.3 \sim V_{IN}+0.3$	V
Continuous Total Power Dissipation	$P_D$	300	mW
Operating Ambient Temperature	$T_{opr}$	-30~+80	°C
Storage Temperature	$T_{stg}$	-40~+125	°C

## Electrical Characteristics

ILC7262 COMMON CHARACTERISTICS  $T_A = 25^\circ\text{C}$

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Supply Voltage	$V_{OUT}$	$V_{IN} = 6.0\text{V}$	4.90	5.0	5.10	V
Input Voltage	$V_{IN}$				10.0	mA

## Electrical Characteristics ILC7262

$V_{OUT}$  SECTION:  $V_{OUT}(T) = 5.0\text{V}$ ,  $T_A = 25^\circ\text{C}$

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Output Voltage	$V_{OUT}$	$I_{OUT} = 40\text{mA}$ , $V_{IN} = 6.0\text{V}$	4.90	5.0	5.10	V
Maximum Output Current	$I_{OUT(max)}$	$V_{IN} = 6.0\text{V}$ , $V_{OUT} \geq 4.5\text{V}$	250			mA
Load Stability	$\Delta V_{OUT}$	$V_{IN} = 6.0\text{V}$ , $1\text{mA} \leq I_{OUT} \leq 100\text{mA}$		40	80	mV
Input/Output Voltage Differential	$V_{dif}$	$I_{OUT} = 100\text{mA}$ $I_{OUT} = 200\text{mA}$		120 380	300 600	mV
Input Stability	$\frac{\Delta V_{OUT}}{\Delta V_{IN} \cdot V_{OUT}}$	$I_{OUT} = 40\text{mA}$ $6.0\text{V} \leq V_{IN} \leq 10.0\text{V}$		0.2	0.3	%/V
Output Voltage Temperature Characteristics	$\frac{\Delta V_{OUT}}{\Delta T_{opr} \cdot V_{OUT}}$	$I_{OUT} = 40\text{mA}$ $-30^\circ\text{C} \leq T_{opr} \leq 80^\circ\text{C}$		±100		ppm/°C

## Electrical Characteristics ILC7262

V<sub>OUT2</sub> SECTION: V<sub>OUT(T)</sub> = 3.3V, T<sub>A</sub> = 25°C







Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Output Voltage	V <sub>OUT</sub>	I <sub>OUT</sub> = 40mA, V <sub>IN</sub> = 6.0V	3.234	3.30	3.37	V
Maximum Output Current	I <sub>OUT(max)</sub>	V <sub>IN</sub> = 6.0V, V <sub>OUT</sub> ≥ 2.97V	165			mA
Load Stability	ΔV <sub>OUT</sub>	V <sub>IN</sub> = 6.0V, 1mA ≤ I <sub>OUT</sub> ≤ 80mA		45	90	mV
Input/Output Voltage Differential	V <sub>dif</sub>	I <sub>OUT</sub> = 80mA I <sub>OUT</sub> = 160mA		180 400	360 700	mV
Input Stability	$\frac{\Delta V_{OUT}}{\Delta V_{IN} \cdot V_{OUT}}$	I <sub>OUT</sub> = 40mA 6.0V ≤ V <sub>IN</sub> ≤ 10.0V		0.2	0.3	%/V
Output Voltage Temperature Characteristics	$\frac{\Delta V_{OUT}}{\Delta T_{opr} \cdot V_{OUT}}$	I <sub>OUT</sub> = 40mA -30°C ≤ T <sub>opr</sub> ≤ 80°C		±100		ppm/°C

## Electrical Characteristics ILC7262

V<sub>OUT2</sub> SECTION: V<sub>OUT(T)</sub> = 3.0V, T<sub>A</sub> = 25°C

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Output Voltage	V <sub>OUT</sub>	I <sub>OUT</sub> = 40mA, V <sub>IN</sub> = 6.0V	2.94	3.0	3.06	V
Maximum Output Current	I <sub>OUT(max)</sub>	V <sub>IN</sub> = 6.0V, V <sub>OUT</sub> ≥ 2.7V	150			mA
Load Stability	ΔV <sub>OUT</sub>	V <sub>IN</sub> = 6.0V, 1mA ≤ I <sub>OUT</sub> ≤ 80mA		45	90	mV
Input/Output Voltage Differential	V <sub>dif</sub>	I <sub>OUT</sub> = 80mA I <sub>OUT</sub> = 160mA		180 400	360 700	mV
Input Stability	$\frac{\Delta V_{OUT}}{\Delta V_{IN} \cdot V_{OUT}}$	I <sub>OUT</sub> = 40mA 6.0V ≤ V <sub>IN</sub> ≤ 10.0V		0.2	0.3	%/V
Output Voltage Temperature Characteristics	$\frac{\Delta V_{OUT}}{\Delta T_{opr} \cdot V_{OUT}}$	I <sub>OUT</sub> = 40mA -30°C ≤ T <sub>opr</sub> ≤ 80°C		±100		ppm/°C

# Typical Performance Characteristics General conditions for all curves



## Ordering Information

Product Number	Package
ILC7262CS-50/30	Dual 50mA 5V & 3.0V Regulator
ILC7262CS-50/33	Dual 50mA 5V & 3.3V Regulator
ILC7262CS-33/30	Dual 125mA 5V to 3.0V & 3.3V Converter

### DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.